





Commonly used in:

Air Conditioner, Heat Pump, Refrigeration, Pool & Sauna Installations.

Working Temperatures:

-20°C to 80°C Dry / 60°C Wet / 70°C Oil

Standard Colors:

Machine Tool Gray



Non-Metallic A/C Whips

Bergen's Non-Metallic Liquidtight A/C Whip Kits come completely assembled and ready to install. Three (3) Conductors are included with either 1/2" or 3/4" Non-Metallic Liquid Tight Conduit using either 8 or 10 AWG THHN Conductors. 4ft & 6ft lengths include standard 1/2" or 3/4"straight and 90-degree compression type fitting for hassle free hook up. 6" wire leads are exposed at each end with 1/2" insulation stripped. UL Listed and meets the requirements of the 2017 National Electrical Code

ITEM #	ITEM DESCRIPTION	Master Pack QTY
1. =141 //	TIZIII ZZGOTIII TIGIK	mactor r don Q11
BACWNM843	4ft Liquid Tight (2) x #8 Stranded, Red/black, (1) x #10 Green. (1) x 3/4" Straight & (1) x 3/4" 90°	1/Bag, 6 Bags/Master
BACWNM863	6ft Liquid Tight (2) x #8 Stranded, Red/Black, (1) x #10 Green. (1) x 3/4" Straight & (1) x 3/4" 90°	1/Bag, 6 Bags/Master
BACWNM1043	4ft Liquid Tight 3 x #10 Stranded, Red/Black/Green, (1) x 1/2" Straight & (1) x 1/2" 90°	1/Bag, 6 Bags/Master
BACWNM1063	6ft Liquid Tight 3 x #10 Stranded, Red/Black/Green, (1) x 1/2" Straight & (1) x 1/2" 90°	1/Bag, 6 Bags/Master

CONTACT US: 800.875.1846